# **Dynaline Sander**

## **Air-Powered In-Line Finishing Sander**



**SANDING PADS PAGE 235** 

**ACCESSORIES PAGE 222** 

**BALL-SWIVEL PLUG PAGE 223** 

> **DYNAJET PAGE 224**

#### Great on Wood, Composites & Solid Surfaces

- 2,400 strokes per minute at 90 PSIG (6.2 Bar).
- Uses adhesive-backed coated and non-woven nylon sheets and rolls.
- · Quality constructed pad is weight-mated to tool for low vibration, smooth operation and superior finishes.
- Comfort platform provides additional hand and wrist support.



In-Line Motion (All models on page)

Sanding Pad can be rotated 360° for adjusting to most efficient

Includes Comfort Platform

position per application.

FOR ABRASIVE SHEETS 2-3/4" x 8" (70 mm x 203 mm) **FOR ABRASIVE ROLLS** 2-3/4" (203 mm) wide SEE PAGES 277, 286



#### Non-Vacuum

#### Model 57400

non-vacuum Sanding Pad (57454).



### **57405 Versatility Kit**

 Includes 57400 Dynaline: 57852 Sanding Pad (3-2/3" wide x 7" long premium urethane, long nap, Hook-Face pad); plus medium grade (94951) and very fine (94956) abrasive impregnated non-woven nylon sheets.

#### Model 57407 with Clips

- Includes 2-3/4" wide x 8" long vinyl-face non-vacuum Sanding Pad with clips (57460).
- · Accepts abrasives 2-3/4" wide x 11" long.
- Up to four abrasive sheets may be attached, ideal for high-production workplaces.



#### Self-Generated Vacuum

#### Model 57401

- Includes 2-3/4" wide x 8" long vinyl-face, vacuum sanding pad (57455).
- · Ready for connection to optional portable self-contained dust collection systems.



#### **Central Vacuum**

#### Model 57404

- Includes 2-3/4" wide x 8" long vinyl-face, vacuum sanding pad (57455).
- Has 1" outside diameter vacuum port for easy central vacuum hose connection.

See page 235 for Dynabrade Sanding Pads!



Model Number	Motor hp (W)	Motor RPM	Sound Level	Maximum Air Flow SCFM (L/Min)	Hose I.D. Size Inch (mm)	Air Inlet Thread	Weight Pound (kg)	Length Inch (mm)	Height Inch (mm)
57400	.3 (186)	2,400	79 dB(A)	18 (510)	1/4 (6)	1/4" NPT	2.6 (1.2)	7 (178)	3-3/4 (95)
57401	.3 (186)	2,400	79 dB(A)	18 (510)	1/4 (6)	1/4" NPT	2.6 (1.2)	7 (178)	3-3/4 (95)
57404	.3 (186)	2,400	80 dB(A)	18 (510)	1/4 (6)	1/4" NPT	2.6 (1.2)	7 (178)	3-3/4 (95)
57407	.3 (186)	2,400	79 dB(A)	18 (510)	1/4 (6)	1/4" NPT	2.6 (1.2)	7 (178)	3-3/4 (95)

Tune-Up Kit: No. 96107 (page 267) • Additional Specifications: Air Pressure 90 PSIG (6.2 Bar)



# 11" Long File Board Sander

## **Air-Powered In-Line Finishing Sander**



SANDING PADS PAGE 239

ACCESSORIES PAGE 222

Ideal for Use on Wood, Metals, Composites and Solid Surfaces

FOR ABRASIVE ROLLS 2-3/4" (70 mm) wide SEE PAGE 286

#### Model 51350

- File board excellent for industrial graining of stainless steel.
- Tool features high quality gear for smooth-running in-line sanding action.



**In-Line Motion** 

- 2,400 strokes per minute. 3/8" (10 mm) long sanding stoke.
- For use with PSA (adhesive-backed) coated and non-woven sheets and rolls.
- Includes 2-3/4" wide x 11" long 57512 Premium Urethane PSA (adhesive-backed) Sanding Pad with clips.
- Also accepts 2-3/4" wide x 11" long pads without clips, and 2-3/4" wide x 8" long non-vacuum pads.







Ultra-smooth in-line sanding action is ideal on wood.

Model	Motor	Strokes	Sound	Maximum Air Flow	Hose I.D. Size	Air Inlet	Weight	Length	Height
Number	hp (W)	Per Minute	Level	SCFM (L/Min)	Inch (mm)	Thread	Pound (kg)	Inch (mm)	Inch (mm)
51350	.3 (186)	2,400	81 dB(A)	18 (510)	1/4 (6)	1/4" NPT	3.1 (1.4)	11 (279)	3-3/4 (95)

Tune-Up Kit: No. 96531 (page 267) • Additional Specifications: Air Pressure 90 PSIG (6.2 Bar)

# **Dynabrade Industry Segment and Product Group Catalogs**

Each catalog features **Dynabrade** tool information and applications specific to **key markets!** 

- > Aerospace Industry (D15.02)
- **➤ Wood, Solid Surface & Composites (D11.08)**
- ➤ Tools for Wind Energy Market (D10.01)
- > Vacuum Tools & Accessories (D09.18)
- > "D3" Random Orbital Sanders (D09.08R)



See complete Literature Library at Dynabrade.com!

