

# Dynafine® Detail Sander

## Air-Powered Finishing Sander



**SANDING PADS**  
PAGE 236

**ACCESSORIES**  
PAGE 222

### Excellent for Use in Tight Corners

- Excellent for cleaning wood edges and corners.
- Ideal for use on furniture, shutters, moldings, door jambs, metal parts and much more.
- Features 1/32" dia. orbital action for superior finishes.
- Handle is offset 7° for greater operator comfort and control.
- Uses Hook-Face and PSA (adhesive-backed) coated, non-woven nylon and sponge abrasives.



**Orbital Motion**  
(All models on page)

### Non-Vacuum

#### Model 57900

- Detail Sander includes triangular and tear-drop Hook-Face pads; also includes 94407 Flow-Control Dynaswivel®.



#### 57910 Versatility Kit

- Includes 57900 tool with Hook-Face and PSA (adhesive-backed) pads, 94407 Flow-Control Dynaswivel® (not shown) and an assortment of coated and non-woven nylon abrasives.



Model 58017



Model 57900

### Self-Generated Vacuum

#### Model 58015

- Utilizes tool's exhaust to create strong vacuum suction.
- 1" (25 mm) diameter vacuum port ready for connection to optional portable self-contained dust collection system (such as 50617 Flex-Hose System, sold separately).

*See page 236 for  
Dynabrade Sanding Pads!*

Portable Dust Collection System  
(Optional - See Page 219)

### Central Vacuum

#### Model 58017

- 1-1/4" (32 mm) diameter vacuum port ready for connection to external or central vacuum system.
- Includes Conductive Hose and Cuffs to shield operator from electrostatic discharge (ESD).



**WATCH the  
Dynafine®  
at Work!**



Model 58017

| Model Number | Motor hp (W) | Motor RPM | Sound Level | Maximum Air Flow SCFM (L/Min) | Hose I.D. Size Inch (mm) | Air Inlet Thread | Air Pressure PSIG (Bar) | Weight Pound (kg) | Length Inch (mm) | Height Inch (mm) |
|--------------|--------------|-----------|-------------|-------------------------------|--------------------------|------------------|-------------------------|-------------------|------------------|------------------|
| 57900        | .12 (89)     | 13,000    | 65 dB(A)    | 20 (566)                      | 1/4 (6)                  | 1/4" NPT         | 90 (6.2)                | 1.6 (.7)          | 9 (229)          | 3-3/4 (95)       |
| 58015        | .12 (89)     | 15,000    | 88 dB(A)    | 20 (566)                      | 1/4 (6)                  | 1/4" NPT         | 90 (6.2)                | 1.8 (.8)          | 9 (229)          | 4 (102)          |
| 58017        | .12 (89)     | 15,000    | 85 dB(A)    | 20 (566)                      | 1/4 (6)                  | 1/4" NPT         | 90 (6.2)                | 1.8 (.8)          | 9 (229)          | 4 (102)          |

Tune-Up Kit: No. 96236 (page 267)

# “Backsplash” Sander

## Air-Powered Dynafine® Finishing Sander



**SANDING PADS**  
PAGE 236

**ACCESSORIES**  
PAGE 222

### A Must for All Solid Surface Fabricators

#### Model 58000

- Excellent for fabricating solid surface covered backsplashes; ideal for cleaning metal edges and corners.
- Includes 58021 and 58024 Backsplash Pads, shown below.
- Air motor features 1/32" diameter orbital action for achieving a superior finish.
- Lightweight tool of only 1.6 lbs!
- Low profile housing allows easy access in hard-to-reach areas. Handle is offset 7° for greater operator comfort and control.
- Includes 94407 Dynaswivel® with fingertip air-flow control dial.

#### 58010 Versatility Kit

- Includes tool with all five sanding pads shown below and an assortment of PSA (adhesive-backed) abrasives.


#### Standard Sanding Pads (Included with Tool)

- **58021**  
3/8" Radius
- **58024**  
3/4" Reverse Radius



#### Optional Sanding Pads (Sold Separately)

- **58020**  
1/4" Radius
- **58022**  
1/2" Radius
- **58023**  
5/8" Radius



For optimum performance, use Dynafine® “Backsplash” Sander with 95676 Coupler/Plug Assembly (see page 228).



Orbital Motion



Dynafine® “Backsplash” Sander powers 58021 Sanding Pad (included), for finishing within coved backsplash.



Sander powers 58024 Pad (included) for use on a radiused surface.

| Model Number | Motor hp (W) | Motor RPM | Sound Level | Maximum Air Flow SCFM (L/Min) | Hose I.D. Size Inch (mm) | Air Inlet Thread | Weight Pound (kg) | Length Inch (mm) | Height Inch (mm) |
|--------------|--------------|-----------|-------------|-------------------------------|--------------------------|------------------|-------------------|------------------|------------------|
| 58000        | .12 (89)     | 13,000    | 65 dB(A)    | 20 (566)                      | 1/4 (6)                  | 1/4" NPT         | 1.6 (.7)          | 9 (229)          | 3-3/4 (95)       |

Tune-Up Kit: No. 96236 (page 267) • Additional Specifications: Air Pressure 90 PSIG (6.2 Bar)



# Dynafine® Finger Sander

## Air-Powered Finishing Sander



DYNAJET  
PAGE 224


ACCESSORIES  
PAGE 222

*Excellent for Use in Hard-to-Reach Areas*

### Model 57930

- Ideal for use on wood, varnished surfaces, plastic, composites, painted surfaces, metal and more!
- Tool includes 57932 Offset Sanding Arm (with 1/8" thick sponge platen), 94407 Flow-Control Dynaswivel® (not shown) and an assortment of abrasives.
- Handle is offset 7° for greater operator comfort and control.
- 1/32" dia. orbital action for fine finishes.

FOR ABRASIVE STRIPS  
3/8" x 2" (10 mm x 51 mm)  
3/4" x 2" (19 mm x 51 mm)  
SEE PAGE 286



Orbital Motion



Model  
57930

| Model Number | Motor hp (W) | Motor RPM | Sound Level | Maximum Air Flow SCFM (L/Min) | Hose I.D. Size Inch (mm) | Air Inlet Thread | Weight Pound (kg) | Length Inch (mm) | Height Inch (mm) |
|--------------|--------------|-----------|-------------|-------------------------------|--------------------------|------------------|-------------------|------------------|------------------|
| 57930        | .12 (89)     | 15,000    | 65 dB(A)    | 20 (566)                      | 1/4 (6)                  | 1/4" NPT         | 1.6 (.7)          | 11-3/4 (298)     | 4 (102)          |

Tune-Up Kit: No. 96236 (page 267) • Additional Specifications: Air Pressure 90 PSIG (6.2 Bar)

# Raised Panel Sander

## Air-Powered Dynafine® Finishing Sander



SANDING PADS  
PAGE 236


ACCESSORIES  
PAGE 222

*Perfect for Sanding Raised Panels and Linear Profiles*

### Model 57906

- 57906 Dynafine® includes 57956 Raised Panel Pad (4" long x 3/4" wide), with unique angled edges for sanding in tight corners and on raised panel edges.
- 57956 Raised Panel Pad is a premium urethane, medium density Hook-Face pad (1/2" thick), which accepts both coated abrasive and non-woven nylon sheets.
- Excellent for sanding raised panels and linear profiles. Also ideal for use on furniture, shutters, moldings and more.

FOR ABRASIVE SHEETS  
4" x 3/4" (102 mm x 19 mm)  
SEE PAGE 278



Orbital Motion



Model  
57906



See page 236  
for Dynabrade  
Sanding Pads!

| Model Number | Motor hp (W) | Motor RPM | Sound Level | Maximum Air Flow SCFM (L/Min) | Hose I.D. Size Inch (mm) | Air Inlet Thread | Weight Pound (kg) | Length Inch (mm) | Height Inch (mm) |
|--------------|--------------|-----------|-------------|-------------------------------|--------------------------|------------------|-------------------|------------------|------------------|
| 57906        | .12 (89)     | 13,000    | 65 dB(A)    | 20 (566)                      | 1/4 (6)                  | 1/4" NPT         | 1.6 (.7)          | 9 (229)          | 3-3/4 (95)       |

Tune-Up Kit: No. 96236 (page 267) • Additional Specifications: Air Pressure 90 PSIG (6.2 Bar)

# Dynabug® “Model T”

## Air-Powered Orbital Finishing Sander




**SANDING PADS**  
PAGE 237

**COUPLER/PLUG**  
PAGE 222

### Featheredge, Finish, Sand and Blend

- 3/32" diameter orbital action is ideal for fine finishes.
- Lightweight... only 1 lb.! Palm-style, ergonomic design features low profile grip for greater operator comfort and control.
- Operates 9 SCFM at 90 PSIG. Can be run by as little as 3 horsepower compressor.
- Low maintenance – easy to repair. Turbine-style vaneless air motor needs no oil!
- Easily interchangeable sanding pads. Accepts reattachable and PSA (adhesive-backed) abrasive sheets and discs; coated and non-woven nylon.
- Each model includes 95955 Urethane Inlet Hose.

**FOR ABRASIVE SHEETS**  
4-1/2" x 5-1/2" (114 mm x 140 mm)  
4-1/4" x 4-1/2" (108 mm x 114 mm)  
**FOR ABRASIVE DISCS**  
5", 6" (127 mm, 152 mm)  
**SEE PAGE 269**



**Orbital Motion**

### Non-Vacuum

#### Model 57920 4" x 4-5/16" Pad (with clips)

- Includes 57999 Vinyl-Face Pad.

#### Model 57923 4-1/4" x 4-1/2" “Quarter-Sheet” Pad

- Includes 57998 Hook-Face Pad.

#### Model 57925 4-1/4" x 4-1/2" “Quarter-Sheet” Pad

- Includes 56244 Vinyl-Face Pad.



Model  
57923

**See page 237  
for Dynabrade  
Sanding Pads!**



*Equipped with  
96455 Urethane  
Inlet Hose*  
(All models on page)




Model  
57922

#### Model 57922 5" Diameter

- Includes 56249 Vinyl-Face Pad.

#### Model 57924 5" Diameter

- Includes 56248 Hook-Face Pad.



**Orbital Motion**




Model  
57926

#### Model 57926 6" Diameter

- Includes 56269 Vinyl-Face Pad.

#### Model 57927 6" Diameter

- Includes 56268 Hook-Face Pad.



**Orbital Motion**

| Model Number | Motor RPM | Sound Level | Maximum Air Flow SCFM (L/Min) | Hose I.D. Size Inch (mm) | Air Inlet Thread | Weight Pound (kg) | Length Inch (mm) | Height Inch (mm) |
|--------------|-----------|-------------|-------------------------------|--------------------------|------------------|-------------------|------------------|------------------|
| 57920        | 20,000    | 68 dB(A)    | 9 (255)                       | 1/4 (6)                  | 1/4" NPT         | 1 (.45)           | 5 (127)          | 3 (76)           |
| 57923        | 20,000    | 68 dB(A)    | 9 (255)                       | 1/4 (6)                  | 1/4" NPT         | 1 (.5)            | 5-1/2 (140)      | 3 (76)           |
| 57925        | 20,000    | 68 dB(A)    | 9 (255)                       | 1/4 (6)                  | 1/4" NPT         | 1 (.5)            | 5 (127)          | 3 (76)           |
| 57922        | 20,000    | 68 dB(A)    | 9 (255)                       | 1/4 (6)                  | 1/4" NPT         | 1 (.5)            | 5-1/2 (140)      | 3 (76)           |
| 57924        | 20,000    | 68 dB(A)    | 9 (255)                       | 1/4 (6)                  | 1/4" NPT         | 1 (.5)            | 5-1/2 (140)      | 3 (76)           |
| 57926        | 20,000    | 68 dB(A)    | 9 (255)                       | 1/4 (6)                  | 1/4" NPT         | 1 (.5)            | 5 (127)          | 3 (76)           |
| 57927        | 20,000    | 68 dB(A)    | 9 (255)                       | 1/4 (6)                  | 1/4" NPT         | 1 (.5)            | 5 (127)          | 3 (76)           |

**Tune-Up Kit: No. 96169** (page 267) • Additional Specifications: Air Pressure 90 PSIG (6.2 Bar)

# Dynabug® “Model T”

## Orbital Finishing Sander – Vacuum Models



**SANDING PADS**  
PAGE 237

**COUPLER/PLUG**  
PAGE 222

### Featheredge, Finish, Sand and Blend

- 3/32" diameter orbital action is ideal for fine finishes.
- 1" outside diameter vacuum port for easy vacuum connection.
- All models include 4-1/4" x 4-1/2" “Quarter-Sheet” Pad.

### Self-Generated Vacuum

- Connects to optional portable self-contained dust collection systems (see page 219).

#### Model 58070

- Includes 56286 Vinyl-Face Vacuum Pad.

#### Model 58075

- Includes 56285 Hook-Face Vacuum Pad.

### Central Vacuum

- Ready for connection to external or central vacuum system.

#### Model 57928


- Includes 56286 Vinyl-Face Vacuum Pad.

#### Model 57929

- Includes 56285 Hook-Face Vacuum Pad.



Model 57928



Orbital Motion



Portable Dust Collection System  
(Optional - See Page 219)



(All Vacuum models)

| Model Number | Motor RPM | Sound Level | Maximum Air Flow SCFM (L/Min) | Hose I.D. Size Inch (mm) | Air Inlet Thread | Weight Pound (kg) | Length Inch (mm) | Height Inch (mm) |
|--------------|-----------|-------------|-------------------------------|--------------------------|------------------|-------------------|------------------|------------------|
| 58070        | 16,000    | 82 dB(A)    | 17 (481)                      | 1/4 (6)                  | 1/4" NPT         | 1.5 (0.7)         | 8 (203)          | 4 (102)          |
| 58075        | 16,000    | 82 dB(A)    | 17 (481)                      | 1/4 (6)                  | 1/4" NPT         | 1.5 (0.7)         | 8 (203)          | 4 (102)          |
| 57928        | 20,000    | 73 dB(A)    | 9 (255)                       | 1/4 (6)                  | 1/4" NPT         | 1 (.5)            | 5 (127)          | 3 (76)           |
| 57929        | 20,000    | 73 dB(A)    | 9 (255)                       | 1/4 (6)                  | 1/4" NPT         | 1 (.5)            | 5 (127)          | 3 (76)           |

**Tune-Up Kit: No. 96169** (page 267) • Additional Specifications: Air Pressure 90 PSIG (6.2 Bar)

# Wet Dynabug® “Model T”

## Turbine Air-Powered Orbital Sander




**SANDING PADS**  
PAGE 237

**WET TANK**  
PAGE 255

### Excellent on Primer and Clearcoat

- Each model includes all hardware for self-siphoning with 20 ft. of water hose. Brass weight drops into bucket for ease of use.
- Up to 3/16" diameter orbital action, with adjustable speed control.
- Our unique water feed “through-the-pad” design allows use of standard round wet paper with holes. No special sand paper or hole punch needed!
- Fingertip control valve allows for precise water flow.



Orbital Motion

#### Model 57908 5" Diameter

- Includes 58086 Hook-Face Pad and soft 53978 Interface Pad for contours.

#### Model 57909 6" Diameter

- Includes 58093 Hook-Face Pad and soft 53980 Interface Pad for contours.



Model 57908

**FOR ABRASIVE DISCS**  
5" (127 mm), 6" (152 mm) diameter  
SEE PAGE 275

| Model Number | Motor RPM | Pad Dia. Inch (mm) | Sound Level | Maximum Air Flow SCFM (L/Min) | Hose I.D. Size Inch (mm) | Air Inlet Thread | Weight Pound (kg) | Length Inch (mm) | Height Inch (mm) |
|--------------|-----------|--------------------|-------------|-------------------------------|--------------------------|------------------|-------------------|------------------|------------------|
| 57908        | 20,000    | 5 (127)            | 76 dB(A)    | 17 (481)                      | 1/4 (6)                  | 1/4" NPT         | 1.5 (0.7)         | 8 (203)          | 4 (102)          |
| 57909        | 20,000    | 6 (152)            | 76 dB(A)    | 17 (481)                      | 1/4 (6)                  | 1/4" NPT         | 1.5 (0.7)         | 8 (203)          | 4 (102)          |

**Tune-Up Kit: No. 96169** (page 267) • Additional Specifications: Air Pressure 90 PSIG (6.2 Bar)



# Dynabug® Sander

## Air-Powered "Jitter-Bug" Type Orbital



**SANDING PADS**  
PAGE 237

**BALL-SWIVEL PLUG**  
PAGE 223

**ACCESSORIES**  
PAGE 222

**DYNAJET**  
PAGE 224

### Featheredge, Finish, Sand and Blend

- Precise 3/32" orbital motion is ideal for achieving a controlled, ultra-fine finish on a variety of surfaces.
- 3/16" orbital motion is available for general sanding applications.
- Powerful air motor utilizes 16 SCFM at 90 PSIG.
- Tools have heavy-duty clips to accept traditional 3-2/3" x 9" abrasive sheets (rolls also available).
- Comfort platform provides additional hand and wrist support.

**Includes Comfort Platform**  
(All models on page)



**Orbital Motion**  
(All models on page)

### Non-Vacuum

- Includes premium 57850 Vinyl-Face Sanding Pad, 3-2/3" x 7".

**Model 57810** 3/32" Dia. Orbit

**Model 57800** 3/16" Dia. Orbit



Model 57810

Model 57814

**See page 237**  
**for Dynabrade**  
**Sanding Pads!**

### Self-Generated Vacuum

- Ready for connection to optional portable self-contained dust collection systems.
- Includes premium 57855 Vinyl-Face Sanding Pad for PSA (abrasive-backed) abrasives.

**Model 57811** 3/32" Dia. Orbit

**Model 57801** 3/16" Dia. Orbit



Model 57811

Portable Dust Collection System  
(Optional - See Page 219)

### Central Vacuum

- Has 1" outside diameter vacuum port for easy central vacuum hose hook-up.
- Includes premium 57855 Vinyl-Face Sanding Pad for PSA (abrasive-backed) abrasives.

**Model 57814** 3/32" Dia. Orbit

**Model 57804** 3/16" Dia. Orbit



Model 57814



**WATCH Tool**  
**at Work!**

| Model Number | Motor hp (W) | Motor RPM | Sound Level | Maximum Air Flow SCFM (L/Min) | Hose I.D. Size Inch (mm) | Air Inlet Thread | Weight Pound (kg) | Length Inch (mm) | Height Inch (mm) |
|--------------|--------------|-----------|-------------|-------------------------------|--------------------------|------------------|-------------------|------------------|------------------|
| 57800        | .24 (179)    | 8,000     | 79 dB(A)    | 16 (453)                      | 1/4 (6)                  | 1/4" NPT         | 2.8 (1.3)         | 7-1/4 (184)      | 4-1/4 (108)      |
| 57801        | .24 (179)    | 8,000     | 76 dB(A)    | 16 (453)                      | 1/4 (6)                  | 1/4" NPT         | 2.8 (1.3)         | 7-1/4 (184)      | 4-1/4 (108)      |
| 57804        | .24 (179)    | 8,000     | 80 dB(A)    | 16 (453)                      | 1/4 (6)                  | 1/4" NPT         | 2.8 (1.3)         | 7-1/4 (184)      | 4-1/4 (108)      |
| 57810        | .28 (209)    | 10,000    | 77 dB(A)    | 18 (510)                      | 1/4 (6)                  | 1/4" NPT         | 2.8 (1.3)         | 7-1/4 (184)      | 4-1/4 (108)      |
| 57811        | .28 (209)    | 10,000    | 74 dB(A)    | 18 (510)                      | 1/4 (6)                  | 1/4" NPT         | 2.6 (1.2)         | 7-1/4 (184)      | 4-1/4 (108)      |
| 57814        | .28 (209)    | 10,000    | 81 dB(A)    | 18 (510)                      | 1/4 (6)                  | 1/4" NPT         | 2.6 (1.2)         | 7-1/4 (184)      | 4-1/4 (108)      |

**Tune-Up Kit: No. 96024** (page 267) • Additional Specifications: Air Pressure 90 PSIG (6.2 Bar)

# Dynabug® II

## Air-Powered Orbital Finishing Sander



**SANDING PADS**  
PAGE 237


**BALL-SWIVEL PLUG**  
PAGE 223

**ACCESSORIES**  
PAGE 222

**DYNAJET**  
PAGE 224

### Featheredge, Finish, Sand and Blend

- Powerful .15 hp (112 W), 10,000 RPM air motor. Utilizes just 13 SCFM (368 L/Min) at 90 PSIG (6.2 Bar).
- Precise 3/32" orbital motion is ideal for achieving a controlled, ultra-fine finish on a variety of surfaces.
- Compact size is ideal for all operators, including those with smaller hands.
- Engineered and tested to ensure less tool vibration than any competitive model!
- Lighter tool weight minimizes fatigue. Comfort Platform provides additional hand and wrist support. Perfect for vertical applications.
- Rectangular shape sands deep into corners, where round pads cannot reach.



**Orbital Motion**  
(All models on page)

#### Non-Vacuum

#### Model 58500

- Includes 56315 Hook-Face Sanding Pad, 74 mm wide x 109 mm long (approximately 3" x 4-1/4"), for accepting optional Hook-Face abrasive sheets.

#### Model 58503

- Includes 56317 Hook-Face Sanding Pad, 80 mm wide x 130 mm long (approximately 3-1/4" x 5"), for accepting optional Hook-Face abrasive sheets.

#### Model 58509

- Includes 56355 Vinyl-Face Sanding Pad, 74 mm wide x 109 mm long (approximately 3" x 4-1/4").

#### Model 58507 with Heavy-Duty Clips

- Tool has specially designed pad base assembly with heavy-duty clips. Clips are designed for heavy-duty use, accepting up to four sheets at once. Ideal for high-production workplaces.
- Includes 56354 vinyl-face Sanding Pad, 68 mm wide by 175 mm long (approximately 2-3/4" x 7"). Weight-mated pad screws directly to pad base assembly.
- Accepts optional abrasive sheets cut from 70 mm (2-3/4") wide abrasive rolls. Four sheets of this width may also be cut from sheets 229 mm wide x 280 mm long (9" x 11").

**FOR ABRASIVE SHEETS**  
75 mm x 110 mm (3" x 4-1/4")  
81 mm x 133 mm (3" x 5-1/4")  
100 mm x 148 mm (4" x 5-3/4")  
**SEE PAGE 277**




Model 58503

*Includes Comfort Platform  
(All Dynabug® II models)*



Model 58500

*See page 237  
for Dynabrade  
Sanding Pads!*



Model 58507

Clip

Clip

| Model Number | Motor hp (W) | Motor RPM | Sound Level | Maximum Air Flow SCFM (L/Min) | Hose I.D. Size Inch (mm) | Air Inlet Thread | Weight Pound (kg) | Length Inch (mm) | Height Inch (mm) |
|--------------|--------------|-----------|-------------|-------------------------------|--------------------------|------------------|-------------------|------------------|------------------|
| 58500        | .15 (112)    | 10,000    | 78 dB(A)    | 13 (368)                      | 1/4 (6)                  | 1/4" NPT         | 1.6 (.7)          | 5-3/4 (147)      | 3-1/2 (91)       |
| 58503        | .15 (112)    | 10,000    | 78 dB(A)    | 13 (368)                      | 1/4 (6)                  | 1/4" NPT         | 1.6 (.7)          | 6-1/4 (165)      | 3-1/2 (91)       |
| 58507        | .15 (112)    | 10,000    | 79 dB(A)    | 13 (368)                      | 1/4 (6)                  | 1/4" NPT         | 2.1 (.95)         | 7-1/16 (180)     | 3-3/4 (94)       |
| 58509        | .15 (112)    | 10,000    | 78 dB(A)    | 13 (368)                      | 1/4 (6)                  | 1/4" NPT         | 1.6 (.7)          | 5-3/4 (147)      | 3-1/2 (91)       |

**Tune-Up Kit: No. 98222** (page 267) • Additional Specifications: Air Pressure 90 PSIG (6.2 Bar)



# Dynabug® II

## Air-Powered Orbital Finishing Sander



**SANDING PADS**  
PAGE 237


**BALL-SWIVEL PLUG**  
PAGE 223

**ACCESSORIES**  
PAGE 222

**DYNAJET**  
PAGE 224

### Featheredge, Finish, Sand and Blend

- Precise 3/32" orbital motion is ideal for achieving a controlled, ultra-fine finish on a variety of surfaces.
- Compact size is ideal for all operators, including those with smaller hands.
- Lighter tool weight minimizes fatigue. Comfort Platform provides additional hand and wrist support. Perfect for vertical applications.



**Orbital Motion**  
(All models on page)

**See page 237  
for Dynabrade  
Sanding Pads!**

**FOR ABRASIVE SHEETS**  
75 mm x 110 mm (3" x 4-1/4")  
81 mm x 133 mm (3" x 5-1/4")  
100 mm x 148 mm (4" x 5-3/4")  
**SEE PAGE 277**



**Model  
58502**

### Self-Generated Vacuum

- Self-Generated Vacuum models vacuum through the tool's exhaust. Tool has 1" outside diameter vacuum port, ready for connection to optional dust collection systems. Includes Hook-Face sanding pad, for optional Hook-Face vacuum abrasive sheets.

#### Model 58501

- Includes 56316 Vacuum Sanding Pad, 74 mm wide x 109 mm long (approximately 3" x 4-1/4").

#### Model 58504

- Includes 56319 Vacuum Sanding Pad, 80 mm wide x 130 mm long (approximately 3-1/4" x 5"), with eight vacuum holes.



**Portable Dust Collection System**  
(Optional - See Page 219)

**Model  
58501**

### Central Vacuum

- Central Vacuum models have 1" outside diameter vacuum port, ready for connection to external vacuum source. Includes Hook-Face sanding pad, for optional Hook-Face vacuum abrasive sheets.

#### Model 58502

- Includes 56316 Vacuum Sanding Pad, 74 mm wide by 109 mm long (approximately 3" x 4-1/4").

#### Model 58505

- Includes 56319 Vacuum Sanding Pad, 80 mm wide by 130 mm long (approximately 3-1/4" x 5"), with eight vacuum holes.

#### Model 58506 "Delta Style"

- Includes 56323 "Delta Style" Vacuum Sanding Pad, 99 mm wide (at wider end) by 143 mm long (approximately 4" x 5-3/4"), with seven vacuum holes. Unique pad has curved edges for sanding rounded areas, and pointed tip for reaching into tight corners.



**Model  
58502**

**Model 58506  
"Delta Style"**

**56323  
"Delta Style"  
Pad**

Curved Pad Edge

| Model Number | Motor hp (W) | Motor RPM | Sound Level | Maximum Air Flow SCFM (L/Min) | Hose I.D. Size Inch (mm) | Air Inlet Thread | Weight Pound (kg) | Length Inch (mm) | Height Inch (mm) |
|--------------|--------------|-----------|-------------|-------------------------------|--------------------------|------------------|-------------------|------------------|------------------|
| 58501        | .15 (112)    | 10,000    | 75 dB(A)    | 13 (368)                      | 1/4 (6)                  | 1/4" NPT         | 1.7 (.75)         | 8-1/4 (212)      | 3-1/2 (91)       |
| 58502        | .15 (112)    | 10,000    | 81 dB(A)    | 13 (368)                      | 1/4 (6)                  | 1/4" NPT         | 1.6 (.7)          | 7 (180)          | 3-1/2 (91)       |
| 58504        | .15 (112)    | 10,000    | 75 dB(A)    | 13 (368)                      | 1/4 (6)                  | 1/4" NPT         | 1.7 (.75)         | 8-3/4 (222)      | 3-3/4 (94)       |
| 58505        | .15 (112)    | 10,000    | 81 dB(A)    | 13 (368)                      | 1/4 (6)                  | 1/4" NPT         | 1.6 (.7)          | 7-1/2 (190)      | 3-1/2 (91)       |
| 58506        | .15 (112)    | 10,000    | 81 dB(A)    | 13 (368)                      | 1/4 (6)                  | 1/4" NPT         | 1.6 (.7)          | 8-3/4 (222)      | 3-1/2 (91)       |

**Tune-Up Kit: No. 98222** (page 267) • Additional Specifications: Air Pressure 90 PSIG (6.2 Bar)